MSDS: 1202



Page 1 of 5

Material Safety Data Sheet Artistic Colour Gloss Top Gel

Section 1: Identification of the Substance/Preparation and of the Company/Undertaking

**Product Name:** Artistic Colour Gloss Top Gel

Chemical Name: N/A MSDS Prepared By:

MSDS Initial Approval Date: 9/1/2010

Family: Soak Off Gel Manufacture: Artistic Nail Design, Inc

14509 Best Ave unit B Norwalk, Ca 90650

 Product Use:
 Emergency Phone Number:
 (800) 535-5053

 Product #: 03201
 Information Contacts:
 (714) 635-5110

Section 2: Hazards Identification

# **EMERGENCY OVERVIEW**

This information is based on findings from related or similar materials.



Flammable liquid and vapor!

May be slightly toxic.

May cause moderate skin injury (reddening & swelling).

May cause chemical burn in eye

#### Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry No specific information available.

Eye Contains materials that are essentially nonirritating, but contact may cause slight transient irritation.

Material may act as a Lachrymator (a substance which increases the flow of tears).

Skin Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization.

Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed.

Ingestion May cause gastrointestinal irritation with nausea, vomiting and diarrhea.

Inhalation May cause respiratory tract irritation with presence of monomer. Vapors may cause dizziness or suffocation.

Sub-Chronic Effects No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime skin painting study

with mice showed no evidence of carcinogencity.

NOTE: Refer to Section II, Toxicological Information for Details

Section 3: Composition/Information on Ingredients							
Chemical Identity	CAS#	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Polyurethane Acrylate Oligomer	Exempt	N/E	Di-Hema Trimethylhexyl Dicarbamate*	N/E	N/E	Not Listed	70-75
2-Hydroxyethyl Methacrylate	109-17-1	203-653-1	PEG-4 Dimethacrylate	N/E	N/E	Not Listed	15-20
Ethyl Methacrylate	97-63-2	202-597-5	Ethyl Methacrylate	100 ppm	100 ppm	Not Listed	5-10
Hydroxcyclohexyl phenyl ketone	947-19-3	213-426-9	Hydroxycyclohexyl phenyl ketone	N/E	N/E	Not Listed	1-3
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	Not Listed	0-1
N/E - None Established N/R - Not Reviewed			* See section 16				
Polyurethane Acrylate Oligomer: 2-Hydroxy ethyl methacrylate: Hydroxypropyl Methacrylate: Isobomyl Methacrylate:	Hazard Symbol Hazard Symbol Hazard Symbol Hazard Symbol	: Xi : Xi	Risk Phrases: R36/37/38 Risk Phrases: R36/38, R43 Risk Phrases: R11, R36//3 Risk Phrases: R36, R37, R	7/38, R43	,	S21, S24/25, S26, S41 S2, S9, S16, S29, S33	
See Section 16 for Risk and Safety Phrase Key							

# **Section 4: First Aid Measures**

First Aid for Eye Flush with plenty of water for 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid. Do NOT allow

victim to rub or keep eyes closed.

First Aid for Skin Remove contaminated clothing and wash contact area with soap and water for 15 minutes. Get medical aid if symptoms persist.

Wash clothing before reuse.

First Aid for Inhalation In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer

artifical respiration and seek medical attention.

First Aid for Ingestion Never give anything by mouth to an unconscioius person. Get medical aid. Do NOT induce vomiting. If conscious and alert, rinse

mouth and drink 2 to 4 cupfuls of milk or water.

### **Section 5: Fire Fighting Measures**

EL LB : ( 0E/05)			
Flash Point ("F/"C)   Flammable Limit (VDE/N) 1 of 5   Auto-Ignition Temperature (VOI%)	Auto-ignition Temperature (vol%)	Flammable Limit (VD)% 1 of 5	Flash Point ( °F/ °C)

110°F/43°C Penske-Martin No Data No Data

Method:

Extinguishing Media: Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.

Fire Fighting Instructions: Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering

confined areas where potential for exposure to vapors or products of combustion exists.

Unusual Hazards: High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the

violent rupture of storage vessels or containers. Avoid the use of a stream of water to control fires since frothing can occur.

#### **Section 6: Accidental Release Measures**

Spill or Release Producers:

Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e.g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

# **Section 7: Handling and Storage**

Handling: Ground and bond containers when transferring material. Avoid contact with skin and eyes, and clothing. Use with adequate

ventilation and avoid breathing in vapor. Keep container closed when not in use. Avoid contact with heat, sparks and flame. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential. Do not pressurize, cut, weld, braze, solder, drill, grind, or

expose empty containers to heat, sparks, or open flames.

Material is extremely light sensitive. Use extreme care and do not expose to natural or UV light, unless using material for it's

intended use. Since the material is very photosensitive any type of light may initiate the curing process.

Storage: Product is extremely light sensitive. If exposed to natural light, LED, UVA, UVB or UV any light, material will cure very quickly.

Store in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above

the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times.

Explosion Hazard: High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the

violent rupture of storage vessels or containers.

#### Section 8: Exposure Controls / Personal Protection

Engineering Controls Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations

generating vapors.

Personal Protective Equipment

General: To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance

with the OSHA PPE Standard (29CFR1910.132), or European Standard En166 be conducted before using this product. Provide eye stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or

whole body suit. Nitrile rubber is better than PVC.

Eye / Face Protection: Wear safety glasses. Wear coverall chemical splash goggles and face shield when possibility exists for eye and face contact due

to splashing or spraying material.

Skin Protection: Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile

rubber is better than PVC.

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain

limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations

found in 29 CFR 1910.134 or European Standard EN149.

# **Section 9: Physical and Chemical Properties**

Appearance	Odor & Odor Threshold	pН	Specific Gravity	Viscosity	%Volatile
Clear, semi-viscous liquid	characteristic acrylate odor	NA	(H20=1): 1.14	N/DA	By Volume: <0.5

Boiling Point/Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/A	N/A	(mm Hg) @ 20 C:<0.01	No Data	No Data	No Data	Insoluble

Flash Point ( °F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
110°F/43°C Penske-Martin	No Data	No Data

#### Section 10: Stability and Reactivity

Stability Incapability (Material to Avoid):

Normally Stable Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust

and strong bases. Page 2 of 5

**Hazardous Decomposition Products:** 

**Hazardous Polymerization:** 

Fumes produced when heated to

decomposition may include:

May occur --- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could

result in violent rupture of sealed storage vessels or containers.

carbon monoxide, carbon dioxide

Conditions to Avoid:

Storage<100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization, contamination with incompatible materials.

# **Section 11: Toxicological Information**

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye	
No info available	No info available	No info available	No info available	No info available	
Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.					

Sensitization	Mutagenicity	Sub-chronic Toxicity
No Information Available	No Information Available	No Information Available

# **Section 12: Ecological Information**

#### **Ecotoxicological Information**

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
No Information Available	No Information Available	No Information Available	No Information Avaible	No Information Available

#### **Chemical Fate Information**

Biodegradability	No Information Available
Chemical Oxygen Demand	No Information Available

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated.

Do not allow to enter drinking water supplies, wastewater, or soil.

#### **Section 13: Disposal Considerations**

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member State, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

#### **Section 14: Transport Information**

**DOT (49 CFR 172)** 

Proper Shipping Name: UN1993, Flammable liquids, n.o.s., (ethyl methacrylate, acrylic esters), 3, PGIII

Identification Number: UN1993 Marine Pollutant: No Special Provisions: N/A Emergency Response Guidebook (ERG) #: 128

IATA (DGR):

Proper Shipping Name: UN1993, Flammable liquids, n.o.s., (ethyl methacrylate, acrylic esters), 3, PGIII

Class or Division: 3.2 UN1993 UN or ID Number:

Packaging Instructions:

Emergency Response Guidance (ICAO)#:

IMO (IMDG):

UN1993, Flammable liquids, n.o.s., (ethyl methacrylate, acrylic esters), 3, PGIII Proper Shipping Name:

Class or Division: Un1993 UN or ID Number: Special Provisions & Stowage/Segregation: None

Emergency Schedule (EmS)#:

Other Information: Flash point >43°C

# **Section 15: Regulatory Information**

**US Federal Regulations** 

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act:
	• NONE
	This product does not contain any Class I or Class 2 ODS
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA:
	• NONE
	This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and /or other applications as an indirect food
	additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its
	hazards are:
	Immediate (acute) health hazard
	Delayed (chronic) health hazard
	Reactive hazard
RCRA	This product is considered to be p அதுகாற்மு s graste under RCRA (40 CFR 261) RCRA Code:

	• Ethyl methacrylate, CAS# 97-63-2, RCRA Code: U1118
	Characteristic of Ignitability, RCRA Code: D001
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.
SARA Title III: Section 302 (RQ)	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency
	release notification ("CERCLA" List):
	• Ethyl methacrylate, CAS# 97-63-2, RQ (Lbs): 1000
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under
	Section 311-312 (40 CFR 370). Its hazards are:
	Immediate (acute) health hazard
	Delayed (chronic) health hazard
	Reactive hazard
SARA Title III: Section 313:	This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the
	Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
	• NONE
TSCA Section 8(b) Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture
	notification requirements.
TSCA Significant New Use Rule:	None of the chemicals in this material have a SNUR under TSCA.

#### State Regulations

State Regulations	
CA Right-to-Know Law:	NONE
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
NJ Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
PA Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
FL Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
MN Right-to-Know Law:	NONE

#### International Regulations

CDSL: Canadian Inventory	Ethyl methacrylate CAS #97-63-2 is on the DSL List. WHMIS = B2, D2B.
(on Canadian Transitional List)	Tetraethylene glycol dimethacrylate, CAS # 109-17-1 is not on the DSL List. WHMIS = n/da
	Hydroxycyclohexyl phenyl ketone CAS #947-19-3 is on the DSL List. WHMIS = n/da
	D&C Violet #2, CAS # 81-48-1 is not on the DSL List. WHMIS = n/da

# Labeling according to EC Directives - 1999/45/EC

European Community:





### HNH Base Gel:

- HAZARD SYMBOLS: Xi irritant, F: Flammable
- RISK PHRASES: R22: Harmful if swallowed, R36/38: Irritating to eyes, respiratory system, and skin, R43: May cause sensitization by skin contact.
- SAFETY PHRASES: S18: Handle and open container with care, S24/25: avoid contact with skin and eyes, S36/37: Wear suitable protective clothing and gloves, \$38: in case of insufficient ventilation, wear suitable respiratory equipment, S46: If swallowed seek medical advise immedicatley and show this container or label.

# Section 16: Other Information

### EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

# **Hazard Symbols:**

Xi - Irritants

F - Flammable substances or preparations


#### Risk Phrases:

R11 Highly flammable; R36/37/38 Irritating to eyes, respiratory system and skin; R43 May cause sensitization by skin contact

### Safety Phrases:

S2 Keep out of the reach of children; S3/7 Keep container tightly closed in a cool place; S9 Keep container in a well-ventilated place; S16 Keep away from sources of ignition - No smoking; S21 When using do not smoke; S24/25 Avoid contact with skin and eyes; S26 In case of contact with eyes, rinse immedicately with plenty of water and seek medical advice; S29 Do not empty into drains; S33 Take precautionary measures against static discharges; S37 Wear suitable gloves; S41 In case of fire and/or explosion do not breathe fumes; S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

**Hazard Rating System (Pictograms)** 



This information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).